

Lumber Stencil Wash

General Properties

A very effective cleaning concentrate for the cleaning and paint stripping of stencils used in the lumber industry. Stencil Wash is a metasilicate based flowable powder that will not cake when properly stored and is non-dusting to minimize worker irritation. It is inorganic in nature, non-polluting, non-flammable and has a rapid dissolution rate in clean water

Recommended Uses

For use in a dip tank cleaning process for use on lumber side stencils. Stronger solutions may be used for paint stripping and general Mill cleaning and degreasing.

Product Information

GENERIC TYPE

Sodium metasilicate

RECOMMENDED DILUTION RATE

2 - 3% by volume in clean water

PIGMENT TYPE

N/a

THEORETICAL COVERAGE

N/a

COLOR

N/a

BASES

N/a

VISCOSITY

N/a

FINISH

N/a

TEMPERATURE RESISTANCE (DRY)

N/a

AVERAGE VOLUME SOLIDS

100% Active

V.O.C. AS APPLIED

0 gm/lit.

AVERAGE WEIGHT SOLIDS

N/a

THINNER

Methods of Application

AIRLESS SPRAY

H.V.L.P

CONVENTIONAL

DIP TANK

Recommended

Drying Time - Temperature, Relative Humidity, and Film Thickness will affect dry and re-coat times.

Substrate Temperature	Touch Dry	Hard Dry	Minimum	Overcoat Interval	
				Maximum	Normal

Recommended Topcoat

77010

Surface Preparation

Stencils should be immersed in Wash solution as quickly as possible after use. A light brushing will accelerate paint removal. Do not leave stencils immersed in solution longer than is necessary. Drying with an air gun is recommended before storage of stencil plates. Recommended cleaning tank temperature is 50 C.

Limitations

This product is alkaline in nature Higher tank temperatures or higher concentrations may cause accelerated corrosion to Aluminum or Galvanized surfaces. Evaluate your specific materials and processes prior to use.

Mixing Instructions

Mix 2- 3 parts of 77010 in 100 parts (vol/vol.) clean water. Stir lightly to mix.

Safety Precautions

Refer to MSD Sheet for detailed Health and Safety instructions.

Storage and Handling

FLASH POINT N/a

PRODUCT WEIGHT

STORAGE Store in a dry, secure location. Seal drums tightly between uses.

PACKAGE SIZE 100 kg drums

Some package sizes or colors may be by special order only. Please check with your Cloverdale Representative when ordering.

Warranty Disclaimer

Cloverdale Paint manufactures quality products. In the event that this product is defective or in any way unsuitable for the application for which it is sold, Cloverdale Paint Inc. will replace the product free of charge. The warranty provided by this data sheet is the only warranty or guarantee of quality made in respect of this product by Cloverdale Paint Inc. By purchasing this product the customer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the customer or implied by any applicable law.

Check for recent amendments to this data sheet at www.cloverdalepaint.com/html/catalog_recent_ir.asp



Cloverdale Paint Inc.

6950 King George Boulevard, Surrey, British Columbia, Canada V3W 4Z1

Web Site: www.cloverdalepaint.com Email: helpdesk@cloverdalepaint.com

Phone: 604 596 6261 Fax: 604 597 2677

c40-0030

17-Dec-14