



Lumber Colorant - Tan

General Properties

A highly concentrated pigment stain designed to enhance the appearance of freshly planed dimension lumber. The product contains inert oxide pigments for maximum durability and UV resistance.

Recommended Uses

For spray, flood or dip application to freshly milled lumber. Reductions with clean water from 15:1 to 30:1 are recommended depending on lumber species, moisture content and desired color. This product is compatible with KOP-COAT Sapstain chemicals. Check with your Cloverdale Paint Representative for use with other chemicals.

Product Information

GENERIC TYPE	Stain
PIGMENT TYPE	Inert Oxide Pigments
COLOR	Tan
BASES	N/A
FINISH	Penetrating
AVERAGE VOLUME SOLIDS	20%
AVERAGE WEIGHT SOLIDS	48%

RECOMMENDED FILM THICKNESS	N/A
	See your Cloverdale Representative for project recommendations.
THEORETICAL COVERAGE	Coverage will depend on reduction, application method, moisture content and wood species.
VISCOSITY	N/A
TEMPERATURE RESISTANCE (DRY)	N/A
V.O.C. AS APPLIED	Less than 23 g/L (0.19 lbs/gal)
THINNER	Water

Methods of Application

AIRLESS SPRAY	Speeflo Ensign 35:1 with tip sizes .011" - .013" or equivalent
H.V.L.P.	Not recommended
CONVENTIONAL	Not recommended
BRUSH / ROLLER	Brushing is limited to small areas or touch-up

Drying Time - Temperature, Relative Humidity, and Film Thickness will affect dry and re-coat times.

Substrate Temperature	Touch Dry	Hard Dry	Minimum	Overcoat Interval	
				Maximum	Normal
25°C (77°F)	10 minutes	10 minutes	N/A	N/A	N/A

Recommended Primer

Self Priming

Surface Preparation

Lumber must be clean, dry and freshly planed.

Limitations

Keep from freezing.

Mixing Instructions

Mix well before using. Maintain constant agitation prior to reduction with water.

Safety Precautions

This product is for industrial use only. **Refer to Material Safety Data Sheet for proper health and safety information.**

Storage and Handling

FLASH POINT	N/A
PRODUCT WEIGHT	12.75 lbs/gal (container extra)
STORAGE	Store in a heated location. See your Cloverdale Paint Representative.
PACKAGE SIZE	55 gallon drum, tote tank

Some package sizes or colors may be by special order only. Please check with your Cloverdale Representative when ordering.

Warranty Disclaimer

Cloverdale Paint manufactures quality products. In the event that this product is defective or in any way unsuitable for the application for which it is sold, Cloverdale Paint Inc. will replace the product free of charge. The warranty provided by this data sheet is the only warranty or guarantee of quality made in respect of this product by Cloverdale Paint Inc. By purchasing this product the customer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the customer or implied by any applicable law.

Check for recent amendments to this data sheet at www.cloverdalepaint.com/html/catalog_recent_ir.asp



Cloverdale Paint Inc.
6950 King George Highway, Surrey, British Columbia, Canada V3W 4Z1
Web Site: www.cloverdalepaint.com Email: helpdesk@cloverdalepaint.com
Phone: 604 596 6261 Fax: 604 597 2677