



## TECHNICAL SPECIFICATIONS DATA SHEET

# 43617

## Timberlox Natural Oil Wood Finish

### Product Description

Timberlox Natural Oil Wood Finish is a penetrating water repellent finish which provides long lasting exterior durability while enhancing the natural look of woods such as redwood, cedar and pine. This product inhibits mildew and fungus growth and acts as an effective screen against harmful ultraviolet rays which damage wood fibres.

### Intended Uses

Timberlox Natural Oil Wood Finish is an exterior stain that is ideal for enhancing the "natural look" of new unfinished or previously stained siding, fencing, lattice, dimensional lumber and other vertical and horizontal wood surfaces by accenting the wood's natural grain and texture. This product can be used on exterior or interior wood surfaces.

### Product Data

**Color:**

Cedar

**Drying Time:** (@25°C 50% Relative Humidity)

**Tack Free:** 1 Hour

**Re-Coat:** 12 Hours

**Finish:**

Low Gloss / Penetrating

**Thinner:**

78001 Mineral Spirits

**Bases:**

N/A

**Flash Point (Tag Closed Cup):**

42°C (107°F)

**Vehicle Type:**

Alkyd

**Viscosity:**

15" - 20" #2 Zahn Cup

**Solids by Volume:**

37%

**V.O.C. (Before Thinning):**

494 g/L or 4.11 lbs/gal

**Solids by Weight:**

42%

**Recommended Film Thickness****(Per Coat):**

**Wet:** 3.9 - 7.9 mils (99 - 200 microns)

**Dry:** 1.4 - 2.9 mils (35 - 74 microns)

**Theoretical Coverage (Per Coat):**

200 - 400 ft<sup>2</sup>/gal (19 - 38 m<sup>2</sup>/L)

## Surface Preparation

All surfaces must be clean, dry, free of powdery materials and loose or scaling paint. If mildew is present, surface should be washed with chlorine bleach solution (20% bleach, 1% liquid detergent in water). To avoid lap marks keep a "wet edge" by stopping only at natural breaks such as windows, doors or the natural course of the siding. New smooth wood should be sanded to remove mill glaze prior to painting.

---

## Recommended Primer

<b>Drywall</b>	Not Recommended	<b>Method</b>	Brush or roller.
<b>Wood</b>	Self-Priming	<b>Thinning</b>	Not normally required.
<b>Masonry</b>	Not Recommended	<b>Cleanup</b>	- Use 78001 Mineral Spirits
<b>Steel</b>	Not Recommended		

---

For detailed information please refer to MSDS

Check for recent amendments to this data sheet at [www.cloverdalepaint.com/html/catalog\\_recent\\_ar.asp](http://www.cloverdalepaint.com/html/catalog_recent_ar.asp)

## Safety Precautions

### Warning

CONTAINS PETROLEUM DISTILLATE. HARMFUL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. VAPOUR HARMFUL. COMBUSTIBLE. KEEP OUT OF REACH OF CHILDREN. Keep away from heat, sparks, and open flame. Do not take internally. Avoid contact with eyes and skin, and breathing of vapour or spray mist. Wear an air supplied mask when applying in enclosed areas. Wash thoroughly after handling. Close container after EACH use. USE WITH ADEQUATE VENTILATION.

### First Aid

In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Wash contaminated skin with soap and water. If ingested, call physician or the Poison Control Centre immediately.

---

## Warranty Disclaimer

Cloverdale Paint manufactures quality products. In the event that this product is defective or in any way unsuitable for the application for which it is sold, Cloverdale Paint Inc. will replace the product free of charge. The warranty provided by this data sheet is the only warranty or guarantee of quality made in respect of this product by Cloverdale Paint Inc. By purchasing this product the customer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the customer or implied by any applicable law.



# Cloverdale Paint

---

6950 King George Hwy., Surrey, BC, V3W 4Z1  
Web Site: [www.cloverdalepaint.com](http://www.cloverdalepaint.com) Email: [helpdesk@cloverdalepaint.com](mailto:helpdesk@cloverdalepaint.com)  
Phone: (604) 596-6261 Fax: (604) 597-2677