## **INTEGRITY** • **INNOVATION** • **PERFORMANCE**



## Water Storage Guide AWWA D-102





## WATER STORAGE GUIDE AWWA D-102



	AWWA Designation	Primer	Intermediate	Topcoat
(0CS)	OCS-1-B	Rustex 710 HS	749 Maintenance Enamel	749 Maintenance Enamel
Outside Coating System (OCS)	OCS-1-C	Rustex 710 HS	749 Maintenance Enamel	749 Maintenance Enamel
	OCS-3	Ecologic WB 71199	Ecologic DTM 711 Series WB Acrylic Enamel	Ecologic DTM 711 Series WB Acrylic Enamel
	OCS-4 Alternate	Barrier (Field) Resist 86 (Shop)		Hardtop Optima Polysiloxane
	OCS-5	ClovaPrime 2.8 83021	ClovaPrime 2.8 83021	Armour Shield 837/839/847
	OCS-6	ClovaZinc 3 83003 (Field) ClovaZinc 2 83002 (Shop)	ClovaMastic 8311 series	Armour Shield 837/839/847

	AWWA Designation	Primer	Intermediate	Topcoat	AWWA min DFT
Inside Coating Systems (ICS)	ICS-1	NSP Liquitile 1172		NSP Liquitile 1172	8 mils
		Tank Guard DW		Tank Guard DW	
	ICS-2	NSP Liquitile 1172	NSP Liquitile 1172	NSP Liquitile 1172	12 mils
		Tank Guard DW	Tank Guard DW	Tank Guard DW	
	ICS-3	Tank Guard Zinc	Tank Guard DW	Tank Guard DW	20 mils
ide (	ICS-4	LifeL	Min 25 mils		
lns	ICS-5	*	Tank Guard DW	Tank Guard DW	10 mils
		*	NSP Liquitile 1172	NSP Liquitile 1172	
	ICS-5				10 mils

\*Cloverdale does not recommend Zinc Rich primers for use in immersion service for potable water.



- **1.** All coating systems listed for OCS will meet VOC regulations for Field Applied Coatings.
- **2.** Alternate coatings are available for shop applied coatings, as your Cloverdale Technical Representative.
- **3.** Coatings suggested in this guide conform to the AWWA D102 standard. Systems provided don't not necessarily reflect maximum film builds and may be approved for additional film thickness where required. Consult your Cloverdale Technical Representative fordetails.
- **4.** The system specified is based on new or bare steel substrates. Consult your Cloverdale Technical Representative for optional overcoat systems if applicable.
- **5.** Consult your Cloverdale Technical Representative to ensure the NSF61 and UL certification is valid for the volume of your tank.
- **6.** Coatings shall be applied in accordance with the product TDS.



